

(12) United States Patent

Keener et al.

US 9,408,930 B2 (10) **Patent No.:**

(45) Date of Patent: Aug. 9, 2016

(54) GENERATION OF MICROBIOCIDE INSIDE A PACKAGE UTILIZING A CONTROLLED GAS COMPOSITION

(71) Applicant: PURDUE RESEARCH

FOUNDATION, West Lafayette, IN

(US)

(72) Inventors: **Kevin M. Keener**, Attica, IN (US);

Jeanette L. Jensen, Oxford, IN (US)

Assignee: PURDUE RESEARCH

FOUNDATION, West Lafayette, IN

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

Appl. No.: 14/593,443

Filed: Jan. 9, 2015 (22)

(65)**Prior Publication Data**

> US 2015/0273094 A1 Oct. 1, 2015

Related U.S. Application Data

- (60) Division of application No. 14/004,030, filed as application No. PCT/US2012/028413 on Mar. 9, 2012, now Pat. No. 8,961,894, which is a division of application No. 12/861,106, filed on Aug. 23, 2010, which is a continuation-in-part of application No. 12/726,097, filed on Mar. 17, 2010, now abandoned.
- (60) Provisional application No. 61/306,774, filed on Feb. 22, 2010, provisional application No. 61/162,785, filed on Mar. 24, 2009, provisional application No. 61/451,975, filed on Mar. 11, 2011.
- (51) **Int. Cl.** A61L 9/00 (2006.01)C07C 1/00 (2006.01)

C25D 5/00	(2006.01)
A61L 2/14	(2006.01)
H01J 37/32	(2006.01)
B65B 55/02	(2006.01)

(52) U.S. Cl.

CPC . A61L 2/14 (2013.01); B65B 55/02 (2013.01); H01J 37/32348 (2013.01); H01J 37/32825

(2013.01)

Field of Classification Search

CPC A61L 2/00; A61L 9/22; A61L 12/00 USPC 422/1, 4, 22, 121, 186.04, 305–306; 204/157.15, 164; 205/147, 637; 250/326; 606/41; 600/6; 604/5

See application file for complete search history.

(56)References Cited

U.S. PATENT DOCUMENTS

5,302,343	Α	*	4/1994	Jacob	 A61L 2/14
					204/164

* cited by examiner

Primary Examiner — Monzer R Chorbaji (74) Attorney, Agent, or Firm — Brinks Gilson & Lione

ABSTRACT

An apparatus and method of producing an atmospheric nonequilibrium plasma (ANEP) in a sealed container having a selected working gas and an object to be treated is described. A variety of working gas mixtures including air, O₂, N₂, CO₂, He and Ar, in combination with a range of ionization gradients, voltages and ANEP column lengths was investigated so as to establish effective ranges of the variables using the sterilization of a sample as a measure of effectiveness. Certain combinations of working gas, voltage gradient, voltage or ANEP column length were found to have greater effectiveness. The approach may be used for food products, medical equipment, or other objects where treatment with reactive gas atmospheres is effective.

18 Claims, 6 Drawing Sheets

